

8 oz. Non-woven Gravel Bag

The **8 oz. Non-woven Gravel Bag** is an all purpose sediment control device. Filled with 3/8" natural pea gravel at approximately 40 lbs. per bag and sewn shut eliminating spill-out.



Also available without rock to be filled onsite.

Quick Look

- Material 8 oz. non-woven geotextile
- Flow Rate 90 gpm/ft
- Dimensions 17" x 28" - empty

8 oz. Non-Woven Gravel Bag Material Specifications

PROPERTY	TEST METHOD	ENGLISH	METRIC
MECHANICAL			
Tensile Strength (Grab)	ASTM D-4632	205 lbs	0.91 kN
Elongation	ASTM D-4632	50%	50%
Puncture	ASTM D-4833	110 lbs	.049 kN
Mullen Burst	ASTM D-3786	350 psi	2410 kPa
Trapezoidal Tear	ASTM D-4533	80 lbs	0.36 kN
ENDURANCE			
UV Resistance	ASTM D-4355	70% @ 500 hrs	70% @ 500 hrs
HYDRAULIC			
Apparent Opening Size (AOS) ⁹	ASTM D-4751	80 US Std. Sieve	0.180 mm
Water Flow Rate	ASTM D-4491	90 gm/ft ²	3657 lpm/m ²
Permittivity	ASTM D-4491	1.40 sec ⁻¹	1.40 sec ⁻¹
PHYSICAL			
Mass Per Unit Area	ASTM D-5261	8.0 oz/yd ²	271.2 g/m ²
Thickness	ASTM D-5199	85 mils	2.16 mm
3/8" Pea Gravel	N/A	~40 lbs	~18.14 kg

Dispose of unit in accordance with applicable Federal, state and local environmental laws and regulations.

The user is solely responsible for the compliance with maintenance and disposal laws and regulations.

The manufacturer or seller assumes no responsibility for proper or improper maintenance or disposal.

Proudly made in the USA by:
Pollution Solution, Inc.

Phone (800) 808-1774
Fax (866) 990-1527

www.psibmp.com
info@psibmp.com

