

Silt Sifter® Tube

Like the **Silt Sifter Bag**, the patented **Silt Sifter Tube** is a dual-component sediment control device that is also designed for *filtration* and *high-flow* but is more flexible allowing for customized protection such as around grated drain inlets. The applications are limitless.



2 Silt Sifter Tubes Shown



2 Silt Sifter Tubes Shown

Quick Look

Patent US 6,905,289

- Outer Material High density polyethylene - Poly thread (4) lock stitching
- Filtering Media Aspen wood excelsior**
- Inner Rock Bag Non woven geotextile
- Weight (Dry) ~40 lbs - 3/8" pea gravel
- Dimensions 60"L x 9" Diameter
- UV Rating 85% - 364° flammability point
- Durability 500 lb burst strength
- Maintenance Clean with power wash or strong hose

**Aspen wood excelsior acts as a filter for capturing silt, sediment and soils. Also a cushioning agent to substantially reduce product damage under normal conditions.

Flow Test Results

- Free Flow Water 30 gpm (gallons per minute)
- Sand 29 gpm
- Top Soil 28 gpm
- Clay 24 gpm

Silt Sifter Tube Material Specifications		
PROPERTY	TEST METHOD	DATA
MECHANICAL		
Break Strength (Grab)	ASTM D-5034	Warp: 89 lbs – Fill: 123 lbs
Break Elongation (Grab)	ASTM D-5034	Warp: 59% - Fill: 64%
Tear Strength	ASTM D-5587	Warp: 44 lbs – Fill: 45 lbs
Burst Strength	ASTM D-3786	193 psi
Trapezoidal Tear	ASTM D-4533	80 lbs
ENDURANCE		
UV Resistance	ASTM D-4355	85%
HYDRAULIC		
Flow Rate	ASTM D-4491	~200 gpm
PHYSICAL		
Composition	N/A	Polyethylene 95% Pigment 3% Misc. Additives 2% (Antioxidants, UV Stabilizers)
Weight	ASTM D-3376	4.25 oz/sq-yd

Dispose of unit in accordance with applicable Federal, state and local environmental laws and regulations.

The user is solely responsible for the compliance with maintenance and disposal laws and regulations.

The manufacturer or seller assumes no responsibility for proper or improper maintenance or disposal.

Proudly made in the USA by:
Pollution Solution, Inc.

Phone (800) 808-1774
Fax (866) 990-1527

www.psibmp.com
info@psibmp.com

