

Hi-Viz Yellow Gravel Bag

The **Hi-Viz Yellow Gravel Bag** is an all purpose sediment control device used in areas where high visibility is a must. Filled with 3/8" natural pea gravel at approximately 35 lbs. and sewn shut eliminating spill-out.



Also available without rock to be filled onsite.



Quick Look

- Material Woven monofilament
- Flow Rate 100 gpm/ft
- Dimensions 15" x 26" - empty

| Hi Viz Gravel Bag Material Specification | | | |
|--|-------------|----------------|----------------|
| PROPERTY | TEST METHOD | ENGLISH | METRIC |
| MECHANICAL | | | |
| Tensile Strength (Grab) | ASTM D-1682 | 196 lbs | W280/F |
| Elongation @ Break | ASTM D-4632 | 50% | 50% |
| Puncture Strength | ASTM D-571 | 390 lbs | 500 N |
| ENDURANCE | | | |
| UV Resistance | ASTM D-4355 | 70% @ 2000 hrs | 70% @ 2000 hrs |
| HYDRAULIC | | | |
| Water Flow Rate | ASTM D-4491 | 100 g/min/sf | 3870 l/min/sm |
| PHYSICAL | | | |
| Weight – Typical | ASTM D-5261 | 5 oz | 226.796 g |
| 3/8" Pea Gravel | N/A | ~35 lbs | ~15.88 kg |

Dispose of unit in accordance with applicable Federal, state and local environmental laws and regulations.

The user is solely responsible for the compliance with maintenance and disposal laws and regulations.

The manufacturer or seller assumes no responsibility for proper or improper maintenance or disposal.

Proudly made in the USA by:
Pollution Solution, Inc.

Phone (800) 808-1774
Fax (866) 990-1527

www.psibmp.com
info@psibmp.com

